DVR – ET Series



Main Features

- Available in 8, 16 Channels Models (ET 800, ET 1600)
- Quadplex (Live / Recording / Playback / Networking / Back up at the same time)
- Advanced MPEG 4
- Multiple Video Outputs : VGA, CRT Monitor, Spot, Loopout
- Quick Search function
- Various Backup : CD/DVD-RW, USB stick, Network backup, USB HDD, Removable HDD
- Internal Storage : 4EA HDD
- Accessed By Web Browser (IE)
- Remote Access and Total Management from Client PC
- Static and Dynamic IP Support

Function

Real Time – Live Monitoring
Simultaneously monitor up to 16 Cameras in realtime. Various views including full screen.
Full control of PTZ Cameras.

• Panorama Video Search

The easy to use Search function will help you find the video you need right away. Search by time, date and camera.

Remote Video Search

Login to your system remotely and have access to all saved video. Search by date, camera and time. Save a screenshot or an AVI video file.

Remote System Viewing

Monitor your security cameras from any location with internet access. You can also search for video, Perform backup and control every aspect of your DVR.

Model	ET 800	ET 1600	
Camera Inputs	8 CH	16 CH	
Camera outputs	VGA, CRT Monitor, Loopout		
Compression	Advanced MPEG-4		
Recording Frame	100 fps	100 fps	
Display Frame	200 fps	400 fps	
O/S	Embedded Linux		
Quadplex	Live, Recording, Playback, Networking, Backup at the same time		
Sensor in / Alarm out	8in / 1 out	16in / 4 out	
Audio	1 Channel, G.	1 Channel, G.726Compression	
Live Display	1, 4, 7, 8	1, 4, 7, 9, 10, 13, 16	
System Control	Front Buttons, IR Remote Controller		
Features			
Recording Modes	Always, Motion, Sensor + Motion, Schedule		
Recording Quality	Low, Normal, High, Highest		
Recording Resolution	Half D1(720 x 288), CIF(360 x 288)		
Post Event Recording	1 to 100 seconds		
Motion Sensitivity	Low, Normal, High, Highest (across the screen, no specific area)		
Search Mode	Time and Date / Overapped List / Event / Go to First to Last		
PTZ Control	Possible(17 Protocols: Pelco D/P, Samsung, Honeywell)		
	PTZ Control from Remote S/W		
Back-up	CD, DVD, USB, Network, Removable HDD		
Storage	4EA HDD		
HDD	From 80GB to 500GB / Compatible with Samsung, Seagate, Maxtor, Hitachi		
Communication Port	RS-485(PTZ), RS-232C, Ethernet Lan, USB		
Upgrade	Via USB or Network		
Network	LAN, WAN, Internet, DHCP, DDNS, Static / Dynamic IP		
Network Speed	10 / 100Mbps Base-T Ethernet		
Web	Web access (Only Monitoring)		
Remote S/W	Live, Playback, Backup(JPG, AVI, DVRfile), Setup		
Recovery	Auto reboot maintaining Setup values if there is Power fail		
Multi Connection	CMS (Central Management Software)		
Hardware			
Power	100 V or 240 V selectable, 50/60 Hz		
Dimension	350 (W) x 400(D) x 80(H) mm		
Weight	6KG		

> The specifications are subject to change without prior notice for the products improvement.

The best product & The best industry

